

Aksa Power Generation has been producing industrial generator sets with an innovative compact design and excellence in quality for over 30 years. Aksa has been providing reliable power through three main production plants and over 15 branch offices worldwide.

Alternator (130 °C Rise)	Voltage	Ph	Pf	Hz	Stand-by Ratings		Prime Ratings	
					kW/kVA	Amp	kW/kVA	Amp
Stamford UCI274E	480/277V	3	0.8	60	100/125	150	90/112	135
	440/254V	3	0.8	60	100/125	164	90/112	148
	240/139V	3	0.8	60	100/125	301	90/112	271
	240/120V	3	0.8	60	100/125	301	90/112	271
	208/120V	3	0.8	60	100/125	347	90/112	312
	240/120V	1	1	60	95/95	396	85/85	354

Rating Definition

Stand-by Power (Maximum): Power available at variable load in the event of main power network failure. No over load is permitted.

Prime Power: Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours of operation.

The above ratings represent the engine performance capabilities to conditions specified in accordance with ISO 8528/5 & ISO3046.

Derating may be required for conditions outside of the test conditions.

Codes, Standards & Standard Features

EPA Certified Tier3 – FLEX engine powered generator set for Mobile / Prime Applications.

The Generator set is designed and manufactured in a facility certified to **ISO9001:2008** standards.

Perkins heavy duty four cycle industrial diesel engine delivers low emission, reliable power, fuel efficiency and fast response to load changes.

Non-proprietary control system provides total gen-set system integrated control, protections, metering, automatic starting/stopping with options of remote control, remote display or remote annunciation.

Aksa Power Generation provides **single source responsibility** for the generator set & accessories.

The generator set, with its components, are **prototype tested** and **production tested**.

Marathon industrial generators meet the requirements of BS EN 60034 and the relevant sections of other international standards.

Heavy duty base frame with integral pad **vibration isolators** eliminates the need for under unit spring vibration isolators.

POWER YOUR FUTURE

Engine Data

Manufacturer	Perkins
Model	1104D-E44TAG2
Cylinders	4, in-line
Max. power @ rated rpm; kWm (BHP)	117 (157)
Brake mean effective pressure; kPa	1771
Aspiration & Cooling	Turbo charged air to air charge cooled
Total displacement; L (in ³)	4.4 (268.5)
Bore; in. (mm)	4.13 (105)
Stroke; in. (mm)	5.0 (127)
Compression ratio	16.2:1
Governor type	ECM, ISO8528-G3
Rated rpm	1800
Rotation	Anti-clockwise viewed on flywheel

Engine Electrical System

Charging alternator	12V, Negative Ground
Alternator rating; (amp)	65
Starter motor power; (kW)	3.0
Starter motor rated voltage; (dc)	12
Battery quantity x rating & CCA	1 x 60Ah, 640

Fuel System

Type of injection	Direct
Fuel injection pump	Common rail
Fuel supply connection size	3/8" NPT
Fuel return connection size	3/8" NPT
Max. fuel lift; m (ft)	1 (3.28)
Fuel prime pump	Manual
Max. fuel flow; L/hr (gal/hr)	130 (34.3)
Max. fuel return flow; m ³ /min	0.8
Fuel filter & water separator	Available

Fuel Consumption (gph)

110% Load	7.9
100% Load	7.3
75% Load	5.8
50% Load	4.2

Exhaust System

Exhaust gas flow; (m ³ /min)	20
Max. back pressure; (kPa)	15
Max. exhaust gas temp in manifold; (°C)	506
Exhaust outlet size; (mm)	64

Cooling System

Radiator ambient temp; °C (°F)	50 (122)
Coolant capacity; L (gal)	17 (4.5)
Coolant pump drive	Gear
Thermostat operation range; °C	85-95
Cooling fan type	Pusher
Cooling fan air flow; m ³ /min	224.4
Combustion air flow; m ³ /min	8.5
Engine coolant flow; L/min (gal/min)	169 (44.6)
Heat rejection to coolant and oil; kWt	61
Heat rejection to ambient; kWt	18
Max. restriction of radiator; kPa (in H ₂ O)	0.12
Air filter	2 stage cyclonic / paper element

Lubrication System

Oil capacity; L (gal)	8 (2.1)
Oil cooler	Water cooled
Oil filter	Spin on, replaceable
Oil temp (continuous operation); °C	125
Oil consumption @ full load (as a % of fuel consumption)	0.15

Alternator Data

Manufacturer	STAMFORD
Model	UCI274E
Design	4 Pole, drip proof rotating field
Exciter type	Brushless, self excited P.M.G. option is available
Stator	2/3 winding pitch
Rotor	Single bearing, flexible disc
Leads	12
Voltage regulator	Solid state, Volts/Hz
Insulation	Class H
Temp. rise @ 40°C ambient	125°C Prime
Alternator Cooling	Direct drive centrifugal blower
Max. over-speed; rev/min	2250
Voltage regulator	SE350

kW Rating at 1800rpm/60Hz

480/277V - 3ph – 0.8pf	143
208/120V - 3ph – 0.8pf	128
240/120V - 1ph – 1pf	96

Base-frame & Enclosure

The complete gen-set is mounted entirely on a heavy duty base frame with an integral semi double wall 177gal fuel tank.

Anti vibration isolators are installed between engine/alternator supports and the base frame.

All enclosure parts are designed with module principles without welding.

Enclosure has four doors on each side for easy serviceability and back door for control system.

Exhaust silencer is protected against environmental influences and is internally mounted within enclosure. Exhaust pipe thermally insulated on engine compartment.

All metal enclosure parts are painted by electrostatic polyester powder paint.

Emergency stop switch externally mounted on enclosure.

Control System

DSE7320 is an advanced control system, suitable for a wide variety of single, diesel or gas, gen-set applications. Monitoring and an extensive number of engine parameters, the module displays warnings, shutdowns and engine status information on the back lit LCD screen, illuminated LEDs, remote PC and via SMS text alerts (with external modem).

- UL recognized, NFPA110 Level 1 compatible
- LCD text display, key menu navigation and front panel editing
- Off/Manual/Auto model switch
- Two wire starting/stopping in Auto mode
- Engine exerciser
- IP65 front panel rating with supplied sealing gasket
- Configurable 9 inputs, 8 outputs with expansion capability
- Real time clock provides accurate event logging
- Fully configurable via DSE Configuration Suite PC software
- Remote SCADA monitoring and BMS integration features
- License free PC software

Protections

- Gen. Voltage - under/over
- Gen. Frequency - under/over
- Engine Speed - under/over
- Engine Oil pressure - low
- Engine Temp. - low/high
- Battery Voltage - low/high
- Weak battery
- Fail to start/stop
- Charge fail
- Over current & load(kW/kVA_r)
- Unbalanced load
- Independent Earth Fault
- Reverse Power
- Fuel level - low/high (optional)
- Loss of speed signal

Instruments

- Gen. Voltage (L-L/L-N)
- Gen Frequency
- Engine Speed
- Oil Pressure
- Water Temperature
- Battery Voltage
- Run time
- Engine maintenance due
- Phase sequence
- Pwr. monitoring
(kWh / kVAh / kVA_{rh})
- Power (kW/kVA/kVA_r)
- Power factor
- Gen. Current (L1-L2-L3)
- Earth current

Convenience Panel Accessories

- (2) Two 20A, 120V GFCI receptacles and breakers
- (3) Three 50A, 240V twist lock receptacles and breakers
- 5-15A, 125V inlet receptacles for battery charger and water heater
- Two wire remote start station
- Generator set voltage adjust rheostat
- (5) 400A rated, stud type quick connect cam-locks

Voltage Selector Switch

- Three positions at 480/277V, 208/120V - 3ph & 240/120 - 1ph
- Product of Salzer or Kraus&Naimer

Standard Features & Accessories

- Trailer
- Sound Attenuated Steel Enclosure
- Heavy Duty Steel Base-frame
- Residential Grade Silencer Inside Enclosure
- Flex Fuel Lines
- Oil Drain Valve & Extension
- Convenience Panel
- Voltage Selector Switch – 3 position
- Emergency Stop Switch
- Battery, Battery Rack & Cables
- Battery Charger
- Main Line CB
- Jacket Water Heater
- Operations Manual

Dimensions & Weight & Sound Level

Gen-set Without Fuel

Type	Generator Set Only
L (in.)	123.4
W (in.)	45.8
H (in.)	76.9
Weight (lb)	5450

Sound Level (dBA@23ft) 76

*Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

Trailer - (Optional)


- DOT approved 7000lbs heavy duty dual axle trailer
- Spring axles w/electric brakes
- Breakaway kit with charger
- 7 pin trailer plug

Circuit Breaker

- 400Amp capacity main line circuit breaker
- Shunt trip controller by generator set control

Optional Accessories

- Upsized Alternator
- PMG Excitation
- Alternator Anti-condensation Heater
- 4 Position VSS
- Fuel Level Monitoring on Controller & High Fuel Alarm
- Fuel Line Check Valve
- Oil Temperature Gauge
- Oil Heater
- Battery Charger 10Amp
- Battery Heater Blanket
- Main Line CB (100% rated)
- Remote Monitoring and Control
- Remote Annunciator



AKSA POWER GENERATION USA LLC
371 Exchange Street, West Monroe, LA 71292
Tel: 318.855.8377
Fax: 318.855.8381
E-mail: sales@aksausa.com
Aksa Power Generation USA is a member of



KAZANCI HOLDING