

**36  
kVA** PRIME  
POWER



**UNDER  
50HP!**

Shown equipped with optional  
**SMARTLOAD™**  
LOAD BANK SYSTEM

**PERFORMANCE //**

- 1 - DSE® Digital Control Panel
- 2 - Curbside Electrical Panel
- 3 - Large Electrical Lugs
- 4 - Emergency Stop Button
- 5 - Delta Demand Excitation™
- 6 - Quietech™ Sound Attenuation
- 7 - Lockable Voltage Selector

**MAINTENANCE //**

- 8 - Lift-off Door Hinges
- 9 - Ext. Fuel Tank Connections
- 10 - 110% Fluid Containment
- 11 - Service Extensions
- 12 - Fuel & Containment Drains
- 13 - Removable Trailer Fenders

**CONSTRUCTION //**

- 14 - Powder-coated Steel Enclosure
- 15 - Stainless Steel Hardware
- 16 - Lockable Access Doors
- 17 - Automotive Door Seals
- 18 - 84.5 Gallon Fuel Tank
- 19 - Heavy-Duty Steel Trailer with Lockable Storage



**Kubota®V2403**  
Tier 4 / CARB  
Diesel Engine  
Under 50 HP!



1 | DSEgenset® Digital Control Panel  
Model 7310 MKII



2 | Single-Phase Receptacles  
120V - 20A x 2 | 240V - 50A x 3  
Optional Single Row Cam-Loks™ Shown



7 | Lockable Voltage Selector Switch  
3Φ 277/480V & 139/240V-120/208V  
1Φ 120/240V



9 | External Fuel Tank Connections  
with 3-Way Selection Valve

**BEST-IN-CLASS dBA RATING // 24-HOUR RUNTIME // EXCELLENT MOTOR STARTING**  
**THE INDUSTRY'S HIGHEST-QUALITY MOBILE GENERATORS**

# GENERATOR MODEL SDG40S-8E1

# RUN WITH AIRMAN®

GENERATOR SPECIFICATIONS	SDG40S-8E1
ALTERNATOR TYPE	AIRMAN WYE Winding
<b>STANDBY OUTPUT</b>	
THREE-PHASE AT 240V 3CD-4 WIRE	37.8 kVA / 30.2 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	28.6 kVA / 28.6 kW
<b>PRIME OUTPUT</b>	
THREE-PHASE AT 240V 3CD-4 WIRE	36 kVA / 28.6 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	26 kVA / 26 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), SWITCHABLE	208/220/240/416/440/480
VOLTAGE (SINGLE-PHASE), SWITCHABLE	120/127/139/240/254/277
ARMATURE CONNECTION	Star with Neutral / Zig Zag
EXCITATION	Brushless with AVR
NUMBER OF POLES	4
POWER FACTOR (THREE-PHASE)	0.8
POWER FACTOR (SINGLE-PHASE)	1.0
INSULATION	Class F
VOLTAGE REGULATION	±0.5%
FREQUENCY REGULATION, STEADY STATE	±0.25% of Overall Mean Value
<b>AMPERAGE</b>	
SINGLE-PHASE (120V) - ZIG ZAG	108A x 2
SINGLE-PHASE (240V) - ZIG ZAG	108A
THREE-PHASE (208V)	95A
THREE-PHASE (240V)	86A
THREE-PHASE (480V)	43A
<b>ENGINE MAKE &amp; MODEL</b>	<b>KUBOTA® V2403</b>
ENGINE CONTROL PANEL	DSE® 7310 MKII
EPA TIER 4 / CARB EMISSION CERTIFIED 2021	CARB Exec. Order U-R-025-0944 EPA Cert. No. MKBXL02.4EMC-042
TYPE OF AFTERTREATMENT	DOC, DPF
ENGINE TYPE	Direct Injection 4-Cycle Liquid Cooled Diesel
ASPIRATION	Turbocharged + Turbo After Cooler

ENGINE MAKE & MODEL (Continued)	KUBOTA® V2403
SAE GROSS HP / BHP@1800 RPM	48.3 BHP / 36 kW
HORSEPOWER RATING (@1800 RPM)	44.9 HP / 33 kW
NUMBER OF CYLINDERS	4
DISPLACEMENT	148.5 cu in
ENGINE SPEED	1800 RPM
GOVERNOR TYPE	Electronic
FUEL TYPE	Ultra-low sulfur diesel
DEF CAPACITY	N/A
DEF CONSUMPTION (MAXIMUM)	N/A
DEF RUNTIME @ FULL LOAD	N/A
FUEL TANK CAPACITY	84.5 gal
<b>FUEL CONSUMPTION</b>	
FULL LOAD	2.3 gal/hr
75% LOAD	1.7 gal/hr
50% LOAD	1.2 gal/hr
RUNTIME @ FULL LOAD	37 hrs
FUEL PUMP	Self-priming Electric Fuel Pump
FUEL FILTER TYPE / QUANTITY	Pre-filter/Separator x 1 Fuel Filter x 1
LUBRICATING OIL CAPACITY	2.6 gal
<b>BATTERY</b>	
SYSTEM VOLTAGE	12V
BATTERY CHARGER ALTERNATOR	30 A
QUANTITY	1
COLD CRANKING AMPS	525 CCA
AMP HOURS	75 Ah
<b>COOLING SYSTEM</b>	
COOLING SYSTEM TYPE	Liquid/Air Fin and Tube Radiator, 50/50 Mix
COOLANT CAPACITY	2.5 gal
WATER PUMP TYPE	Impeller
FAN TYPE	Belt-driven Pusher
NOISE LEVEL @ 23 FEET (NO/FULL LOAD)	57 dBA / 61 dBA

ENCLOSURE	
	Positively Charged Ion (E-coat) Electrodeposition Coating, Baking Finish Coating for Weatherproof, and Anti-corrosion and Salt Pollution
PAINT TYPE	
ENCLOSURE METAL / CONSTRUCTION	Steel
GAUGE STEEL	16 Gauge
DOOR HINGES	Stainless Steel
SERVICE ACCESS POINTS HARDWARE	Stainless Steel
SPILL CONTAINMENT	110%
<b>WEIGHTS &amp; DIMENSIONS</b>	
LENGTH x WIDTH x HEIGHT	67" x 31" x 55"
DRY WEIGHT	2,426 lbs
OPERATING WEIGHT	3,065 lbs
TRAILER WEIGHT	1,182 lbs
OPERATING WEIGHT w/ TRAILER (GVWR)	4,247 lbs
<b>TRAILER WEIGHTS &amp; DIMENSIONS</b>	
LENGTH	144"
WIDTH	70"
HEIGHT W/GENERATOR INSTALLED	73"
WEIGHT	1,182 lbs
WHEEL SIZE-TIRE RATING	ST205/75R15 Load Limit C-1820 lbs @ 50 psi
NUMBER OF AXLES / RATING	2 Axles / 3,700 lbs each
BRAKING TYPE	Surge or Electric
LIGHTING TYPE	LED
CERTIFICATIONS USA/DOT COMPLIANT	FMVSS
ADJUSTABLE HITCH HEIGHT	Yes
<b>COMPLIANCE &amp; CERTIFICATIONS</b>	
FLUID CONTAINMENT	110%
USA DOT COMPLIANT	Yes
CSA LISTED	Yes
TRANSPORT CANADA COMPLIANT	Yes
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final

All specifications are subject to change without prior notice. Visit [anacorp.com](http://anacorp.com) for the most current information.

## SMARTLOAD™

### LOAD BANK SYSTEM

- U.S. PATENT PENDING -



SmartLoad™ System



Lock. Battery Disconnect

### ACCESSORIES & OPTIONS

- ◀ SmartLoad™ System
- ◀ Lockable Battery Disconnect
- Single Row Cam-Loks™ (See Front)
- 4-Position Selector Switch
- Engine Block Heater
- Fuel Filter Heater
- Engine Coolant Heater
- Battery Charger
- Battery Blanket
- 600V
- 🇨🇦 CSA Certification
- 5-Yr./7,000-Hr. Ext. Warranty



SOLD AND SERVICED BY

**ANA N. California**  
1315 Vinci Avenue  
Sacramento, CA 95838

**ANA South Carolina**  
1335 Hayne Street  
Spartanburg, SC 29301

**ANA Texas**  
10440 Brockwood Road  
Dallas, TX 75338



**Alliance North America, Inc.**  
Corporate Headquarters  
11100 Hope Street, Cypress, CA 90630

**ANACORP.COM**  
(562) 450-3570 // [sales@anacorp.com](mailto:sales@anacorp.com)



We make your world easier.