



E2.2H-A 2000 Ekip Dip LSI 3p F HR

[Print to PDF](#)

[Buy now](#)

General Information

Extended Product Type:

E2.2H-A 2000 Ekip Dip LSI 3p F HR

Product ID:

1SDA077269R1

EAN:

8015644836924

Catalog Description:

E2.2H-A 2000 Ekip Dip LSI 3p F HR

Long Description:

C.BREAKER SACE EMAX2 E2.2H-A 2000 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSI R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions:

Yes

ABB Site Meeting Group Waste To Landfill Target:

UL 2799 Zero Waste To Landfill Validation available

End Of Life Disassembling Instructions:

[Disassembly instructions Emax 2 E2.2](#)

Environmental Product Declaration - EPD:

[EPD Emax 2 E2.2 UL \(IT\)](#)

Recyclability Rate of the Product acc. to EN45555:

Design for Closing Resource Loops - Standard EN45555 - 79.1 %

Material Compliance

REACH Declaration:

[REACH Declaration ABB Sace circuit breakers](#)

RoHS Information:

[RoHS Declaration ABB Sace circuit breakers](#)

RoHS Status:

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT):

[CMRT - Conflict Minerals Reporting Template](#)

Toxic Substances Control Act - TSCA:

[Toxic Substances Control Act \(TSCA\) declaration](#)

SCIP:

5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy

Environmental

Environmental Information:

Environmental Information:

Ordering

Order Code US and Canada:

Z2HFUKBB000A000000XX

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85362090

Dimensions

Product Net Width:

276 mm

Product Net Height:

371 mm

Product Net Depth / Length:

270 mm

Product Net Weight:

45 kg

Container Information

Package Level 1 Units:

box 1 piece

Package Level 1 Width:

515 mm

Package Level 1 Height:

610 mm

Package Level 1 Depth / Length:

515 mm

Package Level 1 Gross Weight:

50 kg

Package Level 1 EAN:

8015644836924

Additional Information

Product Main Type:

SACE Emax 2

Product Name:

Air Circuit Breaker

Product Type:

Air Circuit Breaker

Version:

F

Technical

Current Type:

AC

Electrical Durability:

Ue =< 508 V 10000 cycle

Ue = 508 ... 635 V 8000 cycle
30 cycles per hour

Mechanical Durability:

25000 cycle
60 cycles per hour

Number of Poles:

3P

Power Loss:

at Rated Operating Conditions per Pole 250 W

Rated Current (I_n):

2000 A

Rated Insulation Voltage (U_i):

AC 635 V

Rated Operational Voltage:

600 V AC

Rated Voltage (U_r):

600 V

Release:

Ekip Dip LSI

Release Type:

EL

Short-Circuit Performance Level:

H

Standards:

UL

Sub-type:

E2.2

Terminal Connection Type:

Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:

(254 V) 85 kA
(508 V) 85 kA
(635 V) 85 kA

Certificates and Declarations

Data Sheet, Technical Information:

[SACE Emax 2 UL Catalog](#)

Declaration of Conformity - CE:

[EC Declaration of Conformity Emax E2.2](#)

Instructions and Manuals:

[Installation, operation and maintenance instructions for the installer and the user - Emax 2 E2.2-E4.2-E6.2](#)

External Classifications and Standards

ETIM 8:

EC000228 - Power circuit-breaker for trafo/generator/installation protection

ETIM 9:

EC000228 - Power circuit-breaker for trafo/generator/installation protection

IDEA Granular Category Code (IGCC):

4926 >> Air circuit breakers

UNSPSC:

39121615

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)

eClass:

V11.1 : 27370409



PRODUCTS

[Offerings A-Z](#)

[Services](#)

[Where to buy](#)

INDUSTRY SOLUTIONS

[Channel partners](#)

[Buildings and infrastructure](#)

[Industrial automation](#)

[Marine](#)

[Oil & gas](#)

[Power generation](#)

INVESTORS

[Investor & shareholder resources](#)

[Quarterly results & annual reports](#)

[Corporate governance](#)

[Calendar, events and publications](#)

COMPANY

[Customer events](#)

[News & media](#)

[Who we are](#)

[Innovation](#)

[Careers](#)

[Sustainability](#)

[Our values](#)

[Supplying](#)



[Provider information](#)

[Privacy Notice](#)

[Cookie settings](#)

© 1995 - 2025 ABB